MINIMA ROUND LED **5701** SKU 1249005

astro



PRODUCT SPECIFICATION

GENERAL

FINISH: Textured White CABLE LENGTH: Not Applicable MAIN MATERIAL: Metal - Aluminium **GROSS WEIGHT:** 0.18 (Kg) D: 97mm DIA: 82mm **DIMENSIONS:** CLASS: CE (Class III) INSTALLATION ORIENTATION: Ceiling Mount IP RATING: IP20 DIA: 76mm/3" **CUT OUT HOLE: BATHROOM ZONE:** Zone 3

RECESS DEPTH: 150 (mm) VOLTAGE: Constant Current 700 (mA)

FIRE RATING: Not Applicable PRODUCT F MARK: Not suitable for covering with thermal insulation

LAMP

LIGHT SOURCE: COB LED MACADAM ELIPSE: 3-Step MAXIMUM WATTAGE: 6.8W UGR: To Be Advised MAXIMUM LAMP LENGTH: Not Applicable **BEAM ANGLE:** To Be Advised LAMP INCLUDED? Yes (Integral) TILT ADJUSTMENT ANGLE: Not Applicable **LUMINOUS FLUX:** 434.2 (lm) **ROTATION ADJUSTMENT ANGLE:** Not Applicable **COLOUR TEMP:** 2700 (K) AVERAGE LIFESPAN: 36,300 (Hrs) CRI: L70: To Be Advised

ELECTRICAL

R9:

SWITCHED: SUPPLY FREQUENCY: No Not Applicable DIMMABLE: Yes DRIVER/BALLAST VOLTAGE: Not Applicable DIMMING METHOD: Control Gear Dependant DRIVER AVERAGE LIFESPAN: Not Applicable **DRIVER OUTPUT CURRENT:** Not Applicable **EFFICACY:** 40.58 (lm/W)

DRIVER OUTPUT VOLTAGE: Not Applicable DRIVER/BALLAST INCLUDED? No

To Be Advised

ADDITIONAL INFORMATION

BOX QUANTITY x 50

Œ



