





Uplights | 1 x powerLED 2,0 W 630 mA | Blue  
**93132B15**



Technical data	
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Optics	Spot
Power	2 W
Current intensity	630mA
CCT / Tonalità	Blue
C.C. / C.V.	CC
Safety class	3
IP	IP67
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Operating temperature	-20°C / +50°C
Driver included	No
Induzione	No
Emergency mode	No
Directional	No
Tilting	No
Walk-over	Yes
Drive-over	No
Cable included	Yes
Cable length	1 m
Resin potting	Yes

Finishing casing	
Material	Brass
Colour	chrome
Processing	Electroplating

Electronics		
	On/Off Driver 180~300V AC	99186
	On/Off Driver 180~300V AC	99179
	On/Off Driver 190~250V AC / 260~360V DC	89420



Uplights | 1 x powerLED 2,0 W 630 mA | Blue  
**93132B15**

Single emission uplights for outdoor application. The blue LED light source with a spot light distribution is composed of 1 powered LEDs.

The device body is made of brass and features a chrome finish, processed by means of electroplating. The ingress protection degree is IP67; the total weight is of 0.180 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 2,0 W. The power supply cable is included and features.

The device features protection class III and can be floor-mounted with an outer casing, code 84918(for concrete or masonry).



Beret\_2Q | Uplights | Accessories  
**93132B15**



Outer casing  
L=87mm, H=60mm, D=60mm

**Code**  
84918