Beret_2Q

Uplights | 1 x powerLED 2,0 W 630 mA | yellow
93134Y15



Technical data	
Installation position	Floor
Installation environment	Outdoor
Light Source	LED
Optics	Spot
Power	2 W
Current intensity	630mA
CCT / Tonalità	yellow
C.C. / C.V.	CC
Safety class	3
IP	IP67
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Operating temperature	-20°C / +50°C
Driver included	No
Induzione	No
Emergency mode	No
Directional	No
Tilting	No
Walk-over	Yes
Drive-over	No
Cable included	Yes
Cable length	1 m
Resin potting	Yes

Finishing casing	
Material	Stainless steel 316L
Colour	steel
Processing	Shot peening

Electronics		
	On/Off Driver 180~300V AC	99186
	On/Off Driver 180~300V AC	99179
	On/Off Driver 190~250V AC / 260~360V DC	89420

Beret_2Q

Uplights | 1 x powerLED 2,0 W 630 mA | yellow
93134Y15

Single emission uplights for outdoor application. The yellow LED light source with a spot light distribution is composed of 1 powerled LEDs.

The device body is made of stainless steel and features a steel finish, processed by means of shot peening. The ingress protection degree is IP67; the total weight is of 0.180 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 2,0 W. The power supply cable is included and features.

The device features protection class III and can be floor-mounted with an outer casing, code 84918(for concrete or masonry).

Beret_2Q

Beret_2Q | Uplights | Accessories
93134Y15

Outer casing
L=87mm, H=60mm, D=60mm

Code
84918