


PRODUCT DATA SHEET

Skydro Ceiling Led 2700K

IP20 🕒 🕼 🕅 Dimmerable: + 🕦 -

TECHNICAL DRAWINGS



DESIGN BY

Ross Lovegrove

DESCRIPTION

Ceiling lamp, a further development of the Hydro series. A series of pebbles forms a bright sky reflecting the light that bounces on its biomorphic surfaces.

FEATURES			
Article Code: Colour: Installation: Environment:	1245W10A Polished chrome Ceiling Indoor	Material: Series: Emission:	Aluminium, steel, ABS Design, Scenarios Indirect
DIMENSIONS			
Height: Depth:	cm 136 cm 42	Glow Wire Test:	960°C
INCLUDED SOURCES			
Category: Number: Watt: Type:	LED 1 29W 0	Color temperature (K): Color Tolerance: CRI:	2700K MacAdam 2SDCM 90
Class:	A		
Watt:	29W	Delivered lumens output (lm) CCT: Efficiency: Efficacy: CRI: Dimmable Typology:	: 1554lm 2700K 58% 53.59lm/W 90 Push
Notes			

Notes

Available in two versions: the first, in which the indirect light comes from a lighting unit integrated into the lamp, the second, in which the indirect light comes from a wall projector that is separate from the lamp. Skydro is a sectional unit that enables numerous elements to be added. To assemble the multiple units it needs - in addition to the basic units (with or without light source) - an assembly kit (template) and cable kits for the electrical connection.



ACCESSORIES

NO IMAGE AVAILABLE	NO IMAGE AVAILABLE	NO IMAGE AVAILABLE
SKYDRO PLAFONE	SKYDRO PLAFONE	SKYDRO PLAFONE
KIT MONTAGGIO	LED KIT CAVI	*
MODULI	COLLEG.	1234010A
1235010A	1246010A	