

Minion_P4



Pendant Luminaires | 220-240 V | 4 x powerLED 28 W 440 mA | CRI 80
8788



Technical data	
Installation position	Wall lights - Ceiling
Installation environment	Indoor
Light Source	LED
Optics	Flood
Light emission direction	downward
Power	28 W
Luminous flux (source)	3744 lm
Frequency	50-60 Hz
CCT / Tonalità	3000 K
Colour rendering index	80 Ra
Safety class	1
IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Driver included	Driver
Induzione	No
Emergency mode	No
Motion sensor	No
Directional	Orientabile
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No

Finishing casing	
Materiale lega	Aluminium
Colour	embossed white RAL 9003
Processing	Coating

Finishing diffuser	
Materiale lega	PMMA
Processing	Satin finishing



Pendant Luminaires | 220-240 V | 4 x powerLED 28 W 440 mA | CRI 80
8788

Single emission pendant luminaires for indoor application. The warm white LED light source with a flood light distribution is composed of 4 topped LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 3744 lm, with a 133.7 lm/W nominal luminous efficacy and an operating lifetime (L80) of 72.6000 hours.

The device body is made of aluminium and features a embossed white ral 9003 finish, processed by means of coating; the diffuser is made of pmma with a satin finishing treatment. The ingress protection degree is IP40;

The total absorbed power is 28 W.

The device features protection class I and can be wall lights or ceiling-mounted.

Illuminotechnical Features	
Luminous flux (source)	3744 lm
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	80 Ra
Life / Failure Ratio	
L80 B0 C0 72.6h	