

Ray Floor 1

by Rodolfo Dordoni, 2006



Floor lamp providing diffused lighting. Steel tube (10 mm diam.) structure, welded, brushed and chrome-plated. Diffuser support disk in die-cast, polished and chrome-plated Zamak alloy. Injection-molded PA6 (nylon) lamp-cover. Color: white. Injection-molded PC (polycarbonate) inner diffuser. Color: 3% opal. Injection-molded elastic PVC (polyvinylchloride) feet. Lathe-shaped aluminum diffusers, painted white on the inside, and shiny white or black on the outside or gray-colored, blown and overlaid glass with glossy external finish. On the cable there is the electronic dimmer which allows the regulation of light brightness.



Mounting Floor
Environment Indoor
Finish White, Glass, Black

Weight 5.0 (met) - 8.0 (glass) Kg

Light sources 1 x LED 8W E27 740lm 2700K [e] cod. RF25323 available DIMMER

1 x LED 8W E27 740lm 3000K [e] cod. RF25317

DIMMER

Emergency Without

Switching On the cable there is the electronic dimmer

which allows the regulation of light brightness

with a dial.

 Voltage
 220-240V

 Power
 MAX 150W

Battery No Supply included Yes

Cord Length 2300 mm

Materials Aluminum, Glass, Steel

Colors F5916030 - Black

F5916009 - White F5915020 - Glass

Certificate (ϵ)



