

GUISE

Design by Stefan Diez.

Reference

2271.

Application

Hanging lamps

Installation type

Surface

Description

Vibia presents a pendant lamp with two glass pieces where the light source is invisible, emanating directly from the material.

Diffuser

Difusor de vidrio borosilicato transparente

Materials

Profile: Aluminum


Diffuser: Borosilicate glass

Finish



2271-18 Graphite (ADAPTA RF 9913 WX)

Sketch



Electrical characteristics

2 x LED STRIP 24V 20W

Total 40.0 W



Light source: 3000K CRI >90 3484 lm 87 lm/W

Fixture: 1811.27 lm 35.8 lm/W

Driver included: CV - Contant Voltage 110-240V 50/60Hz

Electronic dimming 1-10V

ficha.fichatecnicaproducto.regulacion.opcional DALI

Technical characteristics

- The glass is made of borosilicate. It is typical for the glass to have small air bubbles, some inclusions and tiny scratches. These do not affect the quality or the resistance of the glass.

Physical characteristics

2 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.2654 m³ /

Gross weight 13.0 kg. / Net weight 10.0 kg.


Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 1

Coordinate system : CG

Total flux : 1811.27 lm

Maximum value : 195.12 cd/klm

Light position : C=15.00 G=35.00

Symmetry on the planes : Double symmetrical

Isolux : Isolux (Floor)

Light position :

X=0.00ft Y=0.00ft Z=8.20ft

Certificates

