# LODES

# Nautilus, *design by* Andrea Tosetto, 2017

Ceiling

Strong design and leading—edge technology come together in this family of lamps characterised by a convex lens that projects the LED light wherever its needed or most preferred, for a truly efficient and personalised result. Versatile and dynamic, either on the wall, ceiling or suspended in a variety of versions and finishes, Nautilus lamps satisfy a full range of lighting needs, whether functional or purely decorative, in both residential and professional contexts.



Nautilus Ceiling		Light source F		Frame Aluminium			Diffuser: Aluminium		Code
		LED • 3000 K		( ) Chrome			_		165116
		• 1 × 15W   1210 lm • 220-240V	1210 lm	Matte Black 9005			_		165115
		<ul> <li>CRI 90</li> <li>MacAdam 3-Step</li> <li>LED and driver included</li> </ul>		Matte White 9010			_		165114
				Matte Champagne —					165134
		LED • 2700 K • 1 × 15W   1115 lm • 220-240V	Matte White 9010			_		165111	
			Chrome —			_		165113	
		<ul><li>CRI 90</li><li>MacAdam 3-Step</li><li>LED and driver included</li></ul>		Matte Black 9005			_		165112
				Matte Champagne					165133
	,			<del></del>					
Net weight: 1.10 kg	Gross weight: 1.59 kg	Parcels: N°1	Volume: 0.008 m <sup>3</sup>		C€	IP40	EAC	Energy Saving (	Dim Triac 🕸

lautilus Spot		Light source		Frame Metal				Diffuser: Aluminium		Code
		LED • 2700 K		Matte White 9010			10	_		165135
		• 1 × 10W  8 • 220-240V	350 lm	Matte Black 9005			)5	_		165136
		<ul> <li>CRI 90</li> <li>MacAdam 3-Step</li> <li>LED and driver included</li> </ul>		( ) Chrome				_		165137
				Matte Champagne			ıne	_		165138
		LED • 3000 K		Matte White 9010			10	_		165139
		• 1 x 10W   925 lm • 220-240V • CRI 90 • MacAdam 3-Step	925 lm	Matte Black 9005			_		165140	
			( ) Chrome						165143	
		LED and driver	r included	Matte Champagne			ıne			165144
			1	_						
Net weight: 0.56 kg	Gross weight: 0.94 kg	Parcels: N°1	Volume: 0.005 m <sup>3</sup>			C€	EAE	IP20	Energy Saving 🕸	Dim Triac 🛞

# Polar diagram

# C0-C180 / C90-C270 cd/1000lm

# Nautilus Ceiling

- LED
   2700 K
   1 × 10W |850 lm
- 220-240V
- CRI 90
- MacAdam 3-Step


LED and driver included

- LED 3000 K
- 1 × 10W | 925 lm
- 220-240V
- CRI 90
- MacAdam 3-Step

LED and driver included

Polar diagram

Nautilus Spot



## LED

- 2700 K 1 × 10W |850 lm 220-240V
- CRI 90
- MacAdam 3-Step

LED and driver included

- LED 3000 K
- 1 × 10W | 925 lm
- 220-240V
- CRI 90
- MacAdam 3-Step

LED and driver included

# Other applications of Nautilus



Wall



Suspension