LODES

Nautilus, *design by* Andrea Tosetto, 2017

Wall

Strong design and leading—edge technology come together in this family of lamps characterised by a convex lens that projects the LED light wherever its needed or most preferred, for a truly efficient and personalised result. Versatile and dynamic, either on the wall, ceiling or suspended in a variety of versions and finishes, Nautilus lamps satisfy a full range of lighting needs, whether functional or purely decorative, in both residential and professional contexts.



Nautilus Wall		Light source	Light source		Frame Aluminium			Diffuser: Aluminium		
		LED • 3000 K • 2 × 12W 2420 lm • 220-240V • CRI 90 • MacAdam 3-Step LED and driver included		Matte White 9010			Ma	165151		
				Chrome			Ma	165106		
				() Chrome			() Ch	165108		
			3-Sten	Matte Black 9005			● Ma	165152		
			·	Chrome				Matte Black 9005		
				Matte Champagne			Ma	atte Champagne	165153	
				Matte White 9010			Ma	165148		
		 2700 K 2 × 12W 2230 lm 220-240V CRI 90 MacAdam 3-Step 		Chrome			Ma	165101		
				() Chrome			() Chrome		165103	
				Matte Black 9005			● Ma	165149		
		LED and driver included	·	Chrome			● Ma	165102		
				Matte Champagne			Matte Champagne		165150	
			1	iviatte Cha	ampagr	ie	Ma	atte Cnampagne	100100	
Net weight: 1.15 kg	Gross weight: 1.63 kg	Parcels: N°1	Volume: 0.008 m³		C€	IP40	EHE	Energy Saving (\$	Dim Triac	

LODES

Nautilus Mini		Light source		Frame Metal				Diffuse	r: Aluminium	Code
		LED 2700 K 2 × 6W 1120 lm 220-240V CRI 90 MacAdam 3-Step LED and driver included		Matte Black 9005			5	_		165142
				Matte White 9010				_		165141
		LED • 3000 K • 2 × 6W 1210 lm • 220-240V		Matte White 9010				_		165146
		CRI 90 MacAdam 3-Step LED and driver included		Matte Black 9005			5	_		165147
Net weight: 0.75 kg	Gross weight: 0.95 kg	Parcels: N°1	Volume: 0.008 m³	7		C€	EAC	IP20	Energy Saving (\$	Dim Triac 🗒

Polar diagram

C0-C180 / C90-C270 cd/1000lm

Nautilus Wall


- LED 3000 K
- 2 × 6W | 1210 lm 220-240V
- CRI 90
- MacAdam 3-Step

LED and driver included

- LED
 2700 K
 2 × 6W | 1120 lm
 220-240V
- CRI 90
- MacAdam 3-Step

LED and driver included

Nautilus Mini Polar diagram



LED

- 3000 K 2 × 6W | 1210 lm 220-240V
- CRI 90
- MacAdam 3-Step

LED and driver included

- LED 2700 K
- 2 × 6W | 1120 lm
- 220-240V
- CRI 90
- MacAdam 3-Step

LED and driver included

Other applications of Nautilus





Ceiling

Suspension